Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-035-3762

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.594 inches

Bushing Diameter:

0.250 inches

Overall Height:

0.500 inches

Overall Width:

0.500 inches

Unthreaded Mounting Hole Diameter:

Between 0.100 inches and 0.104 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.340 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.340 inches

Distance From Mounting Shoulder To Front Face:

0.310 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Sma single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping



Contact Surface Treatment: Gold single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Contact Surface Treatment Specification:** Mil-g-45204, ty i, class 1 military specification single treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Contact Material Specification:** Qq-c-530 federal specification single material response single mating end single contact grouping **Shell Material:** Stainless steel **Shell Surface Treatment:** Gold **Shell Surface Treatment Specification:** Mil-g-45204, ty i, class 0 military specification single treatment response **Insert Material Specification:** Mil-p-19468 military specification single material response single mating end **Included Contact Quantity:** 1 single mating end single contact grouping **Included Contact Type:** Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact and body surfaces gold **Precious Material And Weight:** 0.105 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Uns Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.