

View Online at <https://aerobasegroup.com/nsn/5935-00-044-1756>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

2.350 inches

Overall Diameter:

0.781 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

N single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

11000.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thread Length:

0.186 inches

Thread Size:

0.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material:

Gold

Test Data Document:

81349-mil-c-39012 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

81349-mil-c-39012 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.