# NSN 5935-00-044-9490

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-044-9490

view Online at https://aerobasegroup.com/nsn/5955-00-044-9490
Body Style:
Straight shape, rectangular
Overall Length:
2.859 inches
Overall Width:
0.735 inches
Environmental Protection:
Corrosion resistant and moisture resistant and shock resistant and vibration resistant and cold resistant and heat resistant
Unthreaded Mounting Hole Diameter:
0.185 inches
Distance Between Mounting Facility Centers:
2.531 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
50 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification 1st treatment response and qq-s-365 federal specification 2nd treatment response single mating end
single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:

Cadmium and chromate

**Shell Surface Treatment:** 

Aluminum

# NSN 5935-00-044-9490

Electrical Receptacle Connector - Page 2 of 2



#### **Shell Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification all treatment responses

## **Shell Material Specification:**

Qq-a-591 federal specification single material response

## **Insert Material Specification:**

Mil-m-14f, type mdg military specification single material response single mating end

## **Included Contact Quantity:**

50 single mating end single contact grouping

## **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

#### **Precious Material And Weight:**

0.050 gold grains, troy and 0.050 silver grains, troy

#### **Precious Material:**

Gold and silver

#### Shelf Life:

N/a

#### **Unit Of Measure:**

\_\_

#### **Demilitarization:**

No

## Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.