

View Online at <https://aerobasegroup.com/nsn/5935-00-045-8256>

**Body Style:**

Straight shape

**Overall Length:**

Between 1.525 inches and 1.547 inches

**Overall Width:**

Between 0.478 inches and 0.510 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.081 inches and 0.091 inches

**Distance Between Mounting Facility Centers:**

Between 1.307 inches and 1.317 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

"2, 15" single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

125.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

32.0 single mating end single contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Steel

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Included Contact Quantity:**

15 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Special Features:**

Reversed float mounts

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.015 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0