NSN 5935-00-048-6921

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-048-6921

Body Style:

Hood, side opening w/clamp

Overall Length:

3.375 inches

Overall Height:

1.857 inches

Overall Width:

1.250 inches

Cable Entrance Diameter:

0.625 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

24 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Hood, side opening

Connector Locking Method:

Latch

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Contact Material Specification:

Qq-b-750, comp a, spring federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

NSN 5935-00-048-6921

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:

Nickel

N/a

--

No

Shell Surface Treatment Specification: Qq-n-290, cl 2 federal specification single treatment response **Shell Material Specification:** Qq-b-613, comp 4 federal specification single material response **Insert Material Specification:** Mil-m-14, type sdg-f military specification single material response single mating end or mil-m-19833 gdi-30f military specification single material response single mating end **Included Contact Quantity:** 24 single mating end single contact grouping **Included Contact Type:** Leaf spring single mating end single contact grouping **Special Features:** Polarized at positions a, c, 3 and 6 **Precious Material And Location:** Contact surfaces gold **Precious Material:** Gold Shelf Life: Unit Of Measure: **Demilitarization:** Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.