## NSN 5935-00-049-3147



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-049-3147 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 2.641 inches **Overall Height:** 1.400 inches **Overall Width:** 1.745 inches **Distance Between Mounting Facility Centers:** 2.110 inches **Distance From Mounting Shoulder To Front Face:** 0.952 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** "94-525-48, 94-625-48" single mating end **Contact Removability:** Removable single mating end 2nd contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end 3rd contact grouping **Polarization Method:** Mating end Shell Type: Solid Radio Frequency Type Contact Characteristic Impedance In Ohms: 95.0 single mating end all contact groupings **Thread Size:** 0.138 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** 

Gold single mating end all contact groupings

**Insert Material:** 

Rubber synthetic single mating end

## NSN 5935-00-049-3147

Electrical Receptacle Connector - Page 2 of 2



Mil-g-45204 military specification single treatment response single mating end all contact groupings

**Terminal Type:** 

Solder well single mating end 2nd contact grouping

**Shell Material:** 

Aluminum alloy

**Shell Surface Treatment:** 

Cadmium and chromate

**Shell Material Specification:** 

Qq-a-591 federal specification single material response

**Included Contact Quantity:** 

6 single mating end 2nd contact grouping

**Precious Material And Location:** 

Contact surface gold

Precious Material:

Gold

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

-

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.