

View Online at <https://aerobasegroup.com/nsn/5935-00-050-1182>

**Body Style:**

Angle shape w/cable clamp

**Overall Diameter:**

1.188 inches

**Body Angle In Deg:**

90.0

**Environmental Protection:**

Humidity resistant and corrosion resistant and vibration resistant

**Cable Entrance Diameter:**

0.437 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

19-12 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

25.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**Connector Cable Strain Relief Method:**

Cable clamp

**Distance From Centerline To Connector End:**

1.797 inches

**Distance From Centerline To Cable End:**

0.843 inches

**Operating Temperature Rating:**

Between -67.0 degrees celsius and 257.0 degrees celsius

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Rubber single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Included Contact Quantity:**

12 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.012 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.