NSN 5935-00-050-1331

Plug-in Electronic Components Socket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-00-050-1331
Body Material:
Plastic
Fabrication Method:
Molded
Specific Equipment Accommodated:
Relay
Contact Maximum Current Rating In Amps:
5.0
Contact Material:
Copper alloy
Contact Surface Treatment:
Gold
Accommodated Contact Quantity:
20
Polarization Type:
Contact position
Mounting Method:
Saddle
Mounting Type For Which Designed:
Mounting Type For Which Designed: Chassis
Chassis
Chassis Contact Maximum Voltage In Volts And Current Type:
Chassis Contact Maximum Voltage In Volts And Current Type: 2650.0 ac and 2650.0 dc
Chassis Contact Maximum Voltage In Volts And Current Type: 2650.0 ac and 2650.0 dc Precious Material And Location:
Chassis Contact Maximum Voltage In Volts And Current Type: 2650.0 ac and 2650.0 dc Precious Material And Location: Contact surfaces gold
Chassis Contact Maximum Voltage In Volts And Current Type: 2650.0 ac and 2650.0 dc Precious Material And Location: Contact surfaces gold Precious Material And Weight:
Chassis Contact Maximum Voltage In Volts And Current Type: 2650.0 ac and 2650.0 dc Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.020 gold grains, troy
Chassis Contact Maximum Voltage In Volts And Current Type: 2650.0 ac and 2650.0 dc Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.020 gold grains, troy Precious Material:
Chassis Contact Maximum Voltage In Volts And Current Type: 2650.0 ac and 2650.0 dc Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.020 gold grains, troy Precious Material: Gold
Chassis Contact Maximum Voltage In Volts And Current Type: 2650.0 ac and 2650.0 dc Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.020 gold grains, troy Precious Material: Gold Terminal Type And Quantity:
Chassis Contact Maximum Voltage In Volts And Current Type: 2650.0 ac and 2650.0 dc Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.020 gold grains, troy Precious Material: Gold Terminal Type And Quantity: 20 pin
Contact Maximum Voltage In Volts And Current Type: 2650.0 ac and 2650.0 dc Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.020 gold grains, troy Precious Material: Gold Terminal Type And Quantity: 20 pin Shelf Life:
Contact Maximum Voltage In Volts And Current Type: 2650.0 ac and 2650.0 dc Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.020 gold grains, troy Precious Material: Gold Terminal Type And Quantity: 20 pin Shelf Life: N/a
Contact Maximum Voltage In Volts And Current Type: 2650.0 ac and 2650.0 dc Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.020 gold grains, troy Precious Material: Gold Terminal Type And Quantity: 20 pin Shelf Life: N/a
Contact Maximum Voltage In Volts And Current Type: 2650.0 ac and 2650.0 dc Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.020 gold grains, troy Precious Material: Gold Terminal Type And Quantity: 20 pin Shelf Life: N/a Unit Of Measure:
Contact Maximum Voltage In Volts And Current Type: 2650.0 ac and 2650.0 dc Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.020 gold grains, troy Precious Material: Gold Terminal Type And Quantity: 20 pin Shelf Life: N/a Unit Of Measure: Demilitarization: