## NSN 5935-00-051-1527

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-051-1527

Body Style:
Straight shape, external coupling strain relief
Overall Height:
2.385 inches
Overall Width:
2.250 inches
Body Length:
2.932 inches
Unthreaded Mounting Hole Diameter:
0.173 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.750 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
32-6 single mating end
Contact Removability:
Removable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
73.0 single mating end 3rd contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end all contact groupings
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Spring friction
Connector Cable Strain Relief Method:
Cable clamp
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings

**Contact Surface Treatment:** 

Gold single mating end all contact groupings

NSN 5935-00-051-1527 Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic single mating end
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Included Contact Quantity:
3 single mating end 3rd contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.023 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0