## NSN 5935-00-051-2072



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-051-2072 **Body Style:** Straight shape, external coupling **Overall Length:** 1.077 inches **Overall Height:** 1.578 inches **Overall Width:** 1.578 inches **Environmental Protection:** Thermal shock resistant and vibration resistant and moisture resistant and shock resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

**Distance From Mounting Shoulder To Front Face:** 

0.561 inches

**Mating End Quantity:** 

via

**Contact Position Arrangement Style:** 

22-36 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

7.5 single mating end single contact grouping

**Polarization Method:** 

Key, multiple key groove

**Insert Position In Deg:** 

0.0

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet pin

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:** 

Rubber chloroprene class cr single mating end

## NSN 5935-00-051-2072

Electrical Receptacle Connector - Page 2 of 2



## **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1 military specification 2nd treatment response single mating end single contact grouping

## **Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

**Shell Surface Treatment:** 

Cadmium and chromate

**Shell Surface Treatment Specification:** 

Qq-p-416 federal specification single treatment response

**Included Contact Quantity:** 

36 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.036 gold grains, troy and 0.036 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.