NSN 5935-00-051-7132

Electrical Receptacle Connector - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-00-051-7132 |
|---|
| Body Style: |
| Straight shape |
| Overall Length: |
| 2.590 inches |
| Overall Height: |
| 0.840 inches |
| Overall Width: |
| 0.750 inches |
| Environmental Protection: |
| Vibration resistant |
| Distance Between Mounting Facility Centers: |
| Between 2.273 inches and 2.289 inches |
| Threaded Device Type: |
| Mounting stud |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 50 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 7.5 single mating end single contact grouping |
| Polarization Method: |
| Guide pin/socket |
| Connector Locking Method: |
| Spring friction |
| Thread Length: |
| 0.200 inches |
| Thread Size: |
| 0.112 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-19833, type gdi-30 military specification single material response single mating end

NSN 5935-00-051-7132

Electrical Receptacle Connector - Page 2 of 2



| Included Contact Quantity: |
|--|
| 50 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surface gold |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.