## NSN 5935-00-051-8795

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-051-8795

**Body Style:** 

Straight shape, flange mount, external coupling

**Overall Length:** 

1.750 inches

**Overall Height:** 

Between 1.546 inches and 1.578 inches

Overall Width:

Between 1.546 inches and 1.578 inches

**Environmental Protection:** 

Moisture resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

**Cable Entrance Diameter:** 

1.149 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.556 inches and 0.566 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

22-55 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

7.5 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

500.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:** 

700.0 single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet pin

**Connector Cable Strain Relief Method:** 

Potting type

## NSN 5935-00-051-8795

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
55 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.055 gold grains, troy and 0.055 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No