

View Online at <https://aerobasegroup.com/nsn/5935-00-052-2523>

**Body Style:**

Single card type

**Overall Length:**

3.257 inches

**Overall Height:**

0.677 inches

**Overall Width:**

0.352 inches

**Environmental Protection:**

Moisture resistant

**Unthreaded Mounting Hole Diameter:**

0.112 inches

**Distance Between Mounting Facility Centers:**

2.937 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

1 row of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

600.0 single mating end single contact grouping

**Polarization Method:**

Inter-contact polarizing keys

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, ty mdg military specification single material response single mating end

**Included Contact Quantity:**

15 single mating end single contact grouping

**Included Contact Type:**

Flat pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.015 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.