

View Online at <https://aerobasegroup.com/nsn/5935-00-052-3281>

**Thread Direction:**

Right-hand and right-hand and right-hand

**Threaded Device Type:**

Back shell and coupling facility and mounting bushing

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Thready Qty Per Inch (tpi):**

48 and 32 and 32

**Thread Size:**

0.219 inches and 0.312 inches and 0.312 inches

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Silver single mating end single contact grouping

**Insert Material:**

Plastic tetrafluoroethylene single mating end

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver

**Shell Material Specification:**

Qq-b-611a federal specification single material response

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces and shell surface silver

**Precious Material And Weight:**

0.005 silver grains, troy

**Precious Material:**

Silver

**Thread Series Designator:**

Uns and unef and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0