Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-052-5231

# **Body Style:** Straight shape, external coupling **Overall Length:** 1.900 inches **Overall Height:** Between 1.865 inches and 1.885 inches **Overall Width:** Between 1.865 inches and 1.885 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant **Unthreaded Mounting Hole Diameter:** Between 0.145 inches and 0.155 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches **Distance From Mounting Shoulder To Front Face:** Between 0.589 inches and 0.599 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 24-61 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 324.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:**

Plastic single mating end



# **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

# **Terminal Type:**

Solder well single mating end single contact grouping

# Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Cadmium and chromate

## Shell Surface Treatment Specification:

Qq-p-416 federal specification all treatment responses

#### **Included Contact Quantity:**

61 single mating end single contact grouping

## **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

#### **Precious Material And Weight:**

0.061 gold grains, troy and 0.061 silver grains, troy

# **Precious Material:**

Gold and silver

Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

No

#### Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.