NSN 5935-00-054-5853

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-054-5853 **Body Style:** Straight shape **Overall Length:** 1.541 inches **Overall Height:** 0.656 inches **Overall Width:** 0.494 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** 1.312 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end 2nd contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end 2nd contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Back single mating end 2nd contact grouping **Contact Material:** Copper alloy single mating end 2nd contact grouping **Contact Surface Treatment:** Gold and nickel single mating end 2nd contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification 1st treatment response single mating end 2nd contact grouping **Terminal Type:** Solder well single mating end 2nd contact grouping **Shell Material:** Steel **Shell Surface Treatment:**

Chromate and cadmium

NSN 5935-00-054-5853

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Shell Material Specification:

Astm-a-620 assn standard single material response

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.