

View Online at <https://aerobasegroup.com/nsn/5935-00-054-6775>

Thread Class:

2b and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Rectangular shape center screwlock

Overall Length:

3.812 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches

Overall Height:

1.656 inches

Overall Width:

1.531 inches

Environmental Protection:

Humidity resistant and vibration resistant

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

20.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket and polarization boss

Shell Type:

Solid

Connector Locking Method:

Screw lock pin

Thready Qty Per Inch (tpi):

24 and 32

Thread Size:

0.216 inches and 0.138 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Included Contact Quantity:

40 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.040 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.