NSN 5935-00-055-7939

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-055-7939

Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
1.970 inches
Overall Diameter:
1.375 inches
Environmental Protection:
Salt water resistant and humidity resistant and vibration resistant and shock resistant
Cable Entrance Diameter:
0.625 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
18-24 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
315.0
Shell Type:
Solid
Connector Locking Method:
Bayonet slot
Connector Cable Strain Relief Method:
Cable clamp
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate mineral filled single mating end
Terminal Type:
Solder well single mating end single contact grouping

NSN 5935-00-055-7939Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Insert Material Specification:
Mil-m-15 military specification single material response single mating end
Included Contact Quantity:
24 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.024 gold grains, troy and 0.024 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-15 spec.