

View Online at <https://aerobasegroup.com/nsn/5935-00-056-2973>

**Thread Class:**

2a and 2a and 2a

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Straight shape threaded

**Overall Length:**

1.228 inches

**Overall Diameter:**

1.953 inches

**Distance From Mounting Shoulder To Front Face:**

1.072 inches

**Mounting Facility Thickness:**

0.250 inches

**Threaded Device Type:**

Coupling facility and mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Fk-g10 single mating end

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

110.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thready Qty Per Inch (tpi):**

10 and 18

**Thread Size:**

1.375 inches and 1.500 inches

**Insert Material:**

Plastic diallyl phthalate single mating end and glass fiber single mating end

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Anodize

**Insert Material Specification:**

Mil-p-19833, type gdi-30 military specification single material response single mating end

**Bushing Accommodation Hole Shape:**

Round w/flat

**Special Features:**

Contact designation 22-10x

**Thread Series Designator:**

Double stub and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-p-19833 spec.