Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-056-7515

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape threaded
Overall Length:
1.531 inches
Overall Diameter:
2.250 inches
Distance From Mounting Shoulder To Front Face:
1.219 inches
Mounting Facility Thickness:
Between 0.094 inches and 0.360 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
28-21 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
18 and 18
Thread Size:
1.750 inches and 1.750 inches
Terminal Location:
Back single mating end single contact grouping



Contact Material: Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping Shell Material: Aluminum **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 37 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Round pin single mating end single contact grouping **Special Features:** Furnished items - preformed packing **Precious Material And Location:** Contact surfaces silver **Precious Material And Weight:** 0.037 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Uns and uns Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0