NSN 5935-00-057-0125

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-057-0125 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.575 inches **Bushing Diameter:** 0.190 inches **Overall Height:** 0.375 inches **Overall Width:** 0.375 inches **Unthreaded Mounting Hole Diameter:** 0.093 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.232 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.232 inches **Distance From Mounting Shoulder To Front Face:** 0.310 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 36 **Thread Size:** 0.190 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-00-057-0125

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic fluorocarbon single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Anodize
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0