NSN 5935-00-057-0332

Electrical Receptacle Connector Body - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-00-057-0332 |
|---|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape |
| Overall Length: |
| 1.312 inches |
| Overall Height: |
| 0.781 inches |
| Overall Width: |
| 0.375 inches |
| Environmental Protection: |
| Dust resistant and moisture resistant |
| Distance Between Mounting Facility Centers: |
| 1.000 inches |
| Threaded Device Type: |
| Mounting stud |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 9-20 single mating end |
| Polarization Method: |
| Guide pin/socket |
| Connector Locking Method: |
| Friction |
| Thready Qty Per Inch (tpi): |
| 40 |
| Thread Size: |
| 0.112 inches |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Insert Material Specification: |
| Mil-m-14, y sdg-f military specification single material response single mating end |
| Unable To Decode: |
| Unable to decode and unable to decode |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5935-00-057-0332

Electrical Receptacle Connector Body - Page 2 of 2



| _ | | | | | |
|----|-----|---------|-----|---|--|
| 11 | em) | tor | 172 | n | |
| | | | | | |

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.