

View Online at <https://aerobasegroup.com/nsn/5935-00-057-0746>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.604 inches

**Overall Height:**

Between 2.230 inches and 2.270 inches

**Overall Width:**

Between 2.230 inches and 2.270 inches

**Environmental Protection:**

Moisture resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.207 inches and 0.213 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 1.745 inches and 1.755 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.745 inches and 1.755 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.875 inches and 0.891 inches

**Threaded Device Type:**

Coupling facility and back shell

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

32-57 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

23.0 single mating end 2nd contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

900.0 single mating end all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:**

1250.0 single mating end all contact groupings

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thread Length:**

0.625 inches and 0.573 inches

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

2.000 inches and 1.875 inches

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Silver single mating end all contact groupings

**Insert Material:**

Rubber single mating end

**Terminal Type:**

Solder well single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Chromate

**Included Contact Quantity:**

6 single mating end 2nd contact grouping

**Bushing Accommodation Hole Shape:**

Round

**Included Contact Type:**

Round pin single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces silver

**Precious Material And Weight:**

0.016 silver grains, troy

**Precious Material:**

Silver

**Thread Series Designator:**

Uns and un

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0