## NSN 5935-00-057-0746

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-057-0746

**Thread Class:** 

2a and 2a

**Thread Direction:** 

Right-hand and right-hand

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

1.604 inches

**Overall Height:** 

Between 2.230 inches and 2.270 inches

**Overall Width:** 

Between 2.230 inches and 2.270 inches

**Environmental Protection:** 

Moisture resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.207 inches and 0.213 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.745 inches and 1.755 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.745 inches and 1.755 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.875 inches and 0.891 inches

**Threaded Device Type:** 

Coupling facility and back shell

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

32-57 single mating end

**Contact Removability:** 

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:** 

23.0 single mating end 2nd contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

900.0 single mating end all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:** 

1250.0 single mating end all contact groupings

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

Shell Type:

Solid

## NSN 5935-00-057-0746

Electrical Receptacle Connector - Page 2 of 2



Connector Locking Method:
Externally threaded shell
Thread Length:
0.625 inches and 0.573 inches
Thready Qty Per Inch (tpi):
18
Thread Size:
2.000 inches and 1.875 inches
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Silver single mating end all contact groupings
Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Chromate
Included Contact Quantity:
6 single mating end 2nd contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.016 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Uns and un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0