## NSN 5935-00-057-3678

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-057-3678 **Thread Class:** 2a **Body Style:** Straight shape threaded **Overall Length:** 1.280 inches **Overall Diameter:** 1.500 inches **Environmental Protection:** Moisture resistant **Distance From Mounting Shoulder To Front Face:** 0.671 inches **Mounting Facility Thickness:** 0.093 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 37p single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 10.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Ball **Thread Size:** 1.250 inches **Terminal Location:** Back single mating end single contact grouping **Insert Material:** 

Rubber synthetic single mating end

## NSN 5935-00-057-3678

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
37 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round socket single mating end single contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0