Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-057-3678

Thread Class:
2a
Body Style:
Straight shape threaded
Overall Length:
1.280 inches
Overall Diameter:
1.500 inches
Environmental Protection:
Moisture resistant
Distance From Mounting Shoulder To Front Face:
0.671 inches
Mounting Facility Thickness:
0.093 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
37p single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
10.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Ball
Thread Size:
1.250 inches
Terminal Location:
Back single mating end single contact grouping
Insert Material:
Rubber synthetic single mating end
, , ,



**Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy Shell Surface Treatment: Anodize **Included Contact Quantity:** 37 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round Included Contact Type: Round socket single mating end single contact grouping **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0