## NSN 5935-00-057-4297

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-057-4297

Body Style:
Straight shape, external coupling w/backshell
Overall Length:
1.125 inches
Overall Height:
1.438 inches
Overall Width:
1.438 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.187 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.187 inches
Distance From Mounting Shoulder To Front Face:
0.531 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
3719p single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
7.5 single mating end 1st contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Spring friction
Terminal Location:
Back single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings and silver single mating end all contact groupings
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy

NSN 5935-00-057-4297 Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Included Contact Quantity:
6 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end 1st contact grouping
Special Features:
Mod1
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.043 gold grains, troy and 0.043 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0