NSN 5935-00-057-4717



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-057-4717 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.828 inches **Overall Diameter:** 0.438 inches **Cable Entrance Diameter:** 0.161 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Removable single mating end single contact grouping Shell Type: Solid **Connector Cable Strain Relief Method:** Compression nut Radio Frequency Type Contact Characteristic Impedance In Ohms: 750.0 single mating end single contact grouping **Thread Size:** 0.375 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic tetrafluoroethylene single mating end **Terminal Type:** Crimp single mating end single contact grouping

Shell Material: Copper alloy

Shell Surface Treatment:

Gold

NSN 5935-00-057-4717

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 1 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact surface and body surface gold **Precious Material And Weight:** 0.005 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A039b0