NSN 5935-00-057-5233

Electrical Receptacle Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-057-5233



Thread Class: 2b **Thread Direction:** Right-hand **Body Style:** Straight edge type w/mounting flange **Overall Length:** 1.781 inches **Overall Height:** 0.626 inches **Overall Width:** 0.328 inches **Distance Between Mounting Facility Centers:** 1.531 inches **Board Accommodated Length:** 1.078 inches single board **Threaded Device Type:** Mounting hole **Board Accommodated Width:** Between 0.054 inches and 0.071 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Bridged contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Contact to contact polarizing keys **Connector Locking Method:** Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:**

Gold single mating end single contact grouping

NSN 5935-00-057-5233

Electrical Receptacle Connector - Page 2 of 2



| Insert Material: |
|--|
| Plastic diallyl phthalate single mating end |
| Unable To Decode: |
| Unable to decode and unable to decode |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Insert Material Specification: |
| Mil-m-14 military specification single material response single mating end |
| Included Contact Quantity: |
| 10 single mating end single contact grouping |
| Included Contact Type: |
| Leaf spring single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.010 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-m-14 spec. |