

View Online at <https://aerobasegroup.com/nsn/5935-00-057-5736>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape w/jackscrew

Overall Length:

4.128 inches

Overall Height:

2.102 inches

Overall Width:

0.697 inches

Environmental Protection:

Humidity resistant and corrosion resistant and vibration resistant and shock resistant

Unthreaded Mounting Hole Diameter:

0.125 inches

Distance Between Mounting Facility Centers:

3.808 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

244 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

350.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

490.0 single mating end single contact grouping

Polarization Method:

Polarization boss

Connector Locking Method:

Screw

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Crimp single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Included Contact Quantity:

244 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Mod-30; jackscrew type-male and location-center

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.