## NSN 5935-00-057-7591

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-057-7591

**Body Style:** 

Straight shape

**Overall Length:** 

Between 2.714 inches and 2.744 inches

**Overall Height:** 

Between 0.416 inches and 0.436 inches

**Overall Width:** 

Between 0.479 inches and 0.509 inches

**Environmental Protection:** 

Moisture proof and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.125 inches

**Distance Between Mounting Facility Centers:** 

Between 2.495 inches and 2.505 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

37 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Polarization Method:** 

Mating end

Shell Type:

Solid

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:** 

Plastic polyamide single mating end

**Terminal Type:** 

Solder well single mating end single contact grouping

**Shell Material:** 

Steel

**Shell Surface Treatment:** 

Cadmium and chromate

**Included Contact Quantity:** 

37 single mating end single contact grouping

## NSN 5935-00-057-7591

Electrical Receptacle Connector - Page 2 of 2



١	-1-	اء ۽ اء	C		T
m	CIU	ıaea	COL	itact	Type:

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.037 gold grains, troy and 0.037 silver grains, troy

**Precious Material:** 

Gold and silver

## **Test Data Document:**

08288-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

08222-mil-c-24308 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0