NSN 5935-00-058-4909

Electrical Receptacle Connector - Page 1 of 2



/iew Online at https://aerobasegroup.com/nsn/5935-00-058-4909
Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
Between 0.703 inches and 0.734 inches
Overall Height:
Between 1.469 inches and 1.531 inches
Overall Width:
Between 1.469 inches and 1.531 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.151 inches and 1.161 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.151 inches and 1.161 inches
Distance From Mounting Shoulder To Front Face:
Between 0.390 inches and 0.422 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
50, 21-50" single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1250.0 single mating end single contact grouping
Polarization Method:
Contact
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Гhready Qty Per Inch (tpi):
3
Thread Size:
1.312 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-00-058-4909

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Insert Material Specification:
Mil-m-19833, type gdi-30f military specification single material response single mating end
Included Contact Quantity:
50 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.050 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-n-45204 spec