NSN 5935-00-058-7412

Electrical Receptacle Connector - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-00-058-7412 |
|---|
| Body Style: |
| Straight shape |
| Overall Length: |
| 2.650 inches |
| Overall Height: |
| 0.670 inches |
| Overall Width: |
| 0.620 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.120 inches |
| Distance Between Mounting Facility Centers: |
| Between 2.401 inches and 2.411 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 24w7 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 5.0 single mating end single contact grouping |
| Polarization Method: |
| Mating end |
| Shell Type: |
| Solid |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold and silver single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Steel comp 1017 |
| |

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Shell Material Specification:

Qq-s-636 federal specification single material response

Insert Material Specification:

Mil-m-19833, type gdi-30 military specification single material response single mating end

NSN 5935-00-058-7412

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:

17 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Coax contacts to be ordered separately

Precious Material And Location:

Contact surface gold and contact surface silver

Precious Material And Weight:

0.017 gold grains, troy and 0.017 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.