NSN 5935-00-059-1126

Copper alloy

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-059-1126

Thread Class: 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 1.000 inches **Overall Diameter:** 0.625 inches **Mounting Facility Thickness:** 0.094 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Removable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet pin Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping **Thread Size:** 0.375 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Contact Surface Treatment Specification:** Qq-s-365 federal specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:**

NSN 5935-00-059-1126 Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Silver
Shell Surface Treatment Specification:
Qq-s-365 federal specification single treatment response
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Body and contact sufaces silver
Precious Material And Weight:
0.105 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0