

View Online at <https://aerobasegroup.com/nsn/5935-00-059-1163>

Body Style:

Angle, shape, internal coupling

Overall Length:

0.625 inches

Overall Height:

0.516 inches

Overall Diameter:

0.249 inches

Environmental Protection:

Heat resistant and cold resistant and moisture resistant and corrosion resistant and pressure proof and vibration resistant and shock resistant

Cable Entrance Diameter:

0.116 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

400.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

10000.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Spring friction

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204 type 2, cl 2 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold and copper

Shell Surface Treatment Specification:

Mil-g-45204, type 2, cl 2 military specification 1st treatment response and mil-c-14550 military specification 2nd treatment response

Shell Material Specification:

Qq-b-626 federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact and body surfaces gold

Precious Material And Weight:

0.101 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.