## NSN 5935-00-060-0066

Thread Class: 2b and 2a

**Body Style:** 

**Thread Direction:** 

Right-hand and right-hand

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-060-0066

Straight shape
Overall Length:
1.800 inches
Overall Height:
0.770 inches
Overall Width:
0.430 inches
Environmental Protection:
Vibration resistant
Distance Between Mounting Facility Centers:
1.500 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
11 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
32 and 40
Thread Size:
0.164 inches and 0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end

## NSN 5935-00-060-0066

Electrical Receptacle Connector - Page 2 of 2



## Terminal Type: Solder well single mating end single contact grouping Included Contact Quantity: 11 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.011 gold grains, troy and 0.011 silver grains, troy

**Precious Material:** 

Gold and silver

**Thread Series Designator:** 

Unc and unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0