

View Online at <https://aerobasegroup.com/nsn/5935-00-060-2026>

**Body Style:**

Straight shape

**Overall Height:**

15.094 inches

**Overall Diameter:**

4.375 inches

**Environmental Protection:**

Humidity resistant and corrosion resistant and shock resistant

**Cable Entrance Diameter:**

2.406 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

6 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

300.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

416.0 single mating end all contact groupings

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Connector Cable Strain Relief Method:**

Cable clamp

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Silver single mating end all contact groupings

**Insert Material:**

Rubber synthetic single mating end

**Contact Surface Treatment Specification:**

Qq-s-365, type 3 federal specification single treatment response single mating end all contact groupings

**Terminal Type:**

Solder well single mating end all contact groupings

**Contact Material Specification:**

Qq-b-626, comp 22 federal specification single material response single mating end all contact groupings

**Shell Material:**

Rubber synthetic

**Shell Material Specification:**

Astm 735, class scs10, suffix b assn standard single material response

**Included Contact Quantity:**

4 single mating end 2nd contact grouping

**Included Contact Type:**

Round pin single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces silver

**Precious Material And Weight:**

0.030 silver grains, troy

**Precious Material:**

Silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-38159 spec.