

View Online at <https://aerobasegroup.com/nsn/5935-00-060-2026>

Body Style:

Straight shape

Overall Height:

15.094 inches

Overall Diameter:

4.375 inches

Environmental Protection:

Humidity resistant and corrosion resistant and shock resistant

Cable Entrance Diameter:

2.406 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

6 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

300.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

416.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Friction

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Silver single mating end all contact groupings

Insert Material:

Rubber synthetic single mating end

Contact Surface Treatment Specification:

Qq-s-365, type 3 federal specification single treatment response single mating end all contact groupings

Terminal Type:

Solder well single mating end all contact groupings

Contact Material Specification:

Qq-b-626, comp 22 federal specification single material response single mating end all contact groupings

Shell Material:

Rubber synthetic

Shell Material Specification:

Astm 735, class scs10, suffix b assn standard single material response

Included Contact Quantity:

4 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.030 silver grains, troy

Precious Material:

Silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38159 spec.