Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-060-2232

Thread Class:

2a and 2b and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape

Overall Length:

1.070 inches

Overall Height:

0.530 inches

Overall Width:

0.270 inches

Distance Between Mounting Facility Centers:

0.814 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

20 20-20 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1050.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

750.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thread Size:

0.086 inches and 0.086 inches and 0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end



| Terminal Type: |
|--|
| Solder well single mating end single contact grouping |
| Insert Material Specification: |
| Mil-p-14, ty mme military specification single material response single mating end |
| Unable To Decode: |
| Unable to decode and unable to decode |
| Included Contact Quantity: |
| 20 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Special Features: |
| Jackscrew type-female and location-right handandjackscrew type-male and location-left hand |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.020 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unc and unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-p-14 spec. |