NSN 5935-00-060-2445

Body Style:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-060-2445

Straight shape
Overall Length:
1.541 inches
Overall Height:
0.429 inches
Overall Width:
0.308 inches
Environmental Protection:
Moisture resistant and vibration resistant and shock resistant and corrosion resistant
Unthreaded Mounting Hole Diameter:
0.086 inches
Distance Between Mounting Facility Centers:
1.312 inches
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end 1st contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end 1st contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Terminal Location:
Back single mating end 1st contact grouping
Contact Material:
Copper alloy single mating end 1st contact grouping
Contact Surface Treatment:
Gold and silver single mating end 1st contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end 1st contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium and chromate
Insert Material Specification:
Mil-m-14f, type sdg military specification single material response single mating end
Included Contact Quantity:
5 single mating end 1st contact grouping

NSN 5935-00-060-2445

Electrical Receptacle Connector - Page 2 of 2



			-1-	٠.	<u> </u>		-4	Tvi	
ı	IIC	ıu	ue	u	υU	III	CL	1 7 1	JE.

Round socket single mating end 1st contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.005 gold grains, troy and 0.005 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14f spec.