NSN 5935-00-060-5682

Anodize

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-060-5682

View Online at https://aerobasegroup.com/nsn/5935-00-060-5682
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
1.688 inches
Overall Diameter:
0.656 inches
Environmental Protection:
Moisture resistant and vibration resistant
Cable Entrance Diameter:
0.375 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
8-3 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Connector Cable Strain Relief Method:
Cable clamp
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Ceramic single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:

NSN 5935-00-060-5682

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.003 gold grains, troy and 0.003 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0