Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-060-5792

| Thread Class:   |
|---|
| 2a  |
| Thread Direction:   |
| Right-hand  |
| Body Style:   |
| Straight shape, external coupling   |
| Overall Length:   |
| 1.782 inches  |
| Overall Height:   |
| 3.000 inches  |
| Overall Width:  |
| 3.000 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.209 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Height:   |
| 2.375 inches  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 2.375 inches  |
| Distance From Mounting Shoulder To Front Face:                              |
| 0.875 inches  |
| Threaded Device Type:   |
| Coupling facility   |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| 44-52 single mating end   |
| Contact Removability:   |
| Nonremovable single mating end single contact grouping                      |
| Contact Maximum Current Rating In Amps:                                     |
| 22.0 single mating end single contact grouping                              |
| Contact Maximum Ac Voltage Rating In Volts:                                 |
| 500.0 single mating end single contact grouping                             |
| Contact Maximum Dc Voltage Rating In Volts:                                 |
| 700.0 single mating end single contact grouping                             |
| Polarization Method:  |
| Key, multiple key groove  |
| Insert Position In Deg:   |
| 0.0   |
| Shell Type:   |
| Solid   |
| Connector Locking Method:   |
| Externally threaded shell   |
|   |



**Thread Length:** 0.875 inches Thready Qty Per Inch (tpi): 10 **Thread Size:** 2.700 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Rubber synthetic single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Oxide **Shell Surface Treatment Specification:** Mil-f-14072, finish no. E311, type 1 military specification single treatment response **Included Contact Quantity:** 104 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Round socket single mating end single contact grouping **Thread Series Designator:** Double stub Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-f-14072 spec.