

View Online at <https://aerobasegroup.com/nsn/5935-00-060-6782>

Thread Class:

2a and 2b and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape

Overall Length:

1.250 inches

Overall Height:

0.630 inches

Overall Width:

0.380 inches

Environmental Protection:

Vibration resistant and heat resistant and cold resistant and salt water resistant

Distance Between Mounting Facility Centers:

1.032 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

34 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Operating Temperature Rating:

Between -54.0 degrees celsius and 100.0 degrees celsius

Thready Qty Per Inch (tpi):

56 and 56 and 56

Thread Size:

0.086 inches and 0.086 inches and 0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification 1st treatment response and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Insert Material Specification:

Mil-p-19833, ty gdi-30 military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

34 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Jackscrew type-female and location-right hand and jackscrew type-male and location-left hand

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.034 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.