NSN 5935-00-061-7412

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-061-7412

Body Style:
Straight shape, rectangular
Overall Length:
3.969 inches
Overall Height:
0.875 inches
Overall Width:
0.880 inches
Environmental Protection:
Vibration resistant
Unthreaded Mounting Hole Diameter:
0.125 inches
Distance Between Mounting Facility Centers:
3.625 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
32 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
750.0 single mating end single contact grouping
Polarization Method:
Shell
Shell Type:
Solid
Connector Locking Method:
Latch
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping
Shell Material:
Copper alloy

NSN 5935-00-061-7412 Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Nickel
Included Contact Quantity:
32 single mating end single contact grouping
Included Contact Type:
Leaf spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.032 gold grains, troy
Precious Material:
Gold
Reference Number Differentiating Characteristics:
Quality controlled for polaris
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A039b0