## NSN 5935-00-061-9088

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-061-9088 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** Between 1.660 inches and 1.720 inches **Overall Height:** Between 0.948 inches and 0.980 inches **Overall Width:** Between 0.530 inches and 0.590 inches **Distance Between Mounting Facility Centers:** Between 1.240 inches and 1.260 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 20 20-20 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket Thread Length: 0.344 inches **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy

## NSN 5935-00-061-9088

Electrical Receptacle Connector - Page 2 of 2



| Included Contact Quantity:                          |
|---|
| 20 single mating end single contact grouping        |
| Included Contact Type:                              |
| Round pin single mating end single contact grouping |
| Thread Series Designator:                           |
| Unc   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:                                    |
|   |
| Demilitarization:                                   |
| No  |

Fiig: A039b0