Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-061-9269

Thread Class:
2a and 2a
Thread Pitch Diameters:
+0.125 to 0.250 inches
Thread Direction:
Left-hand and left-hand
Body Style:
Straight shape, external coupling w/backshell
Overall Length:
2.625 inches
Overall Height:
2.750 inches
Overall Width:
2.750 inches
Environmental Protection:
Corrosion resistant and pressure proof and vibration resistant and waterproof
Unthreaded Mounting Hole Diameter:
0.203 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
2.094 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.094 inches
2.094 inches
2.094 inches Distance From Mounting Shoulder To Front Face:
2.094 inches Distance From Mounting Shoulder To Front Face: 1.000 inches
2.094 inches Distance From Mounting Shoulder To Front Face: 1.000 inches Threaded Device Type:
2.094 inches Distance From Mounting Shoulder To Front Face: 1.000 inches Threaded Device Type: Back shell and coupling facility
2.094 inches Distance From Mounting Shoulder To Front Face: 1.000 inches Threaded Device Type: Back shell and coupling facility Mating End Quantity:
<ul> <li>2.094 inches</li> <li>Distance From Mounting Shoulder To Front Face:</li> <li>1.000 inches</li> <li>Threaded Device Type:</li> <li>Back shell and coupling facility</li> <li>Mating End Quantity:</li> <li>1</li> </ul>
<ul> <li>2.094 inches</li> <li>Distance From Mounting Shoulder To Front Face:</li> <li>1.000 inches</li> <li>Threaded Device Type:</li> <li>Back shell and coupling facility</li> <li>Mating End Quantity:</li> <li>1</li> <li>Contact Position Arrangement Style:</li> </ul>
2.094 inches Distance From Mounting Shoulder To Front Face: 1.000 inches Threaded Device Type: Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 20-37 single mating end
2.094 inches Distance From Mounting Shoulder To Front Face: 1.000 inches Threaded Device Type: Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 20-37 single mating end Contact Removability:
2.094 inches Distance From Mounting Shoulder To Front Face: 1.000 inches Threaded Device Type: Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 20-37 single mating end Contact Removability: Removable single mating end single contact grouping
2.094 inches Distance From Mounting Shoulder To Front Face: 1.000 inches Threaded Device Type: Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 20-37 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps:
<ul> <li>2.094 inches</li> <li>Distance From Mounting Shoulder To Front Face: <ol> <li>1.000 inches</li> </ol> </li> <li>Threaded Device Type: <ul> <li>Back shell and coupling facility</li> </ul> </li> <li>Mating End Quantity: <ul> <li>1</li> </ul> </li> <li>Contact Position Arrangement Style: <ul> <li>20-37 single mating end</li> <li>Contact Removability:</li> <li>Removable single mating end single contact grouping</li> <li>Contact Maximum Current Rating In Amps: <ul> <li>135.0 single mating end single contact grouping</li> </ul> </li> </ul></li></ul>
<ul> <li>2.094 inches</li> <li>Distance From Mounting Shoulder To Front Face: <ol> <li>1.000 inches</li> </ol> </li> <li>Threaded Device Type: <ul> <li>Back shell and coupling facility</li> </ul> </li> <li>Mating End Quantity: <ul> <li>1</li> </ul> </li> <li>Contact Position Arrangement Style: <ul> <li>20-37 single mating end</li> <li>Contact Removability:</li> <li>Removable single mating end single contact grouping</li> <li>Contact Maximum Current Rating In Amps: <ul> <li>135.0 single mating end single contact grouping</li> </ul> </li> </ul></li></ul>
<ul> <li>2.094 inches</li> <li>Distance From Mounting Shoulder To Front Face: <ol> <li>1.000 inches</li> </ol> </li> <li>Threaded Device Type: <ul> <li>Back shell and coupling facility</li> </ul> </li> <li>Mating End Quantity: <ul> <li>1</li> </ul> </li> <li>Contact Position Arrangement Style: <ul> <li>20-37 single mating end</li> <li>Contact Removability:</li> <li>Removable single mating end single contact grouping</li> <li>Contact Maximum Current Rating In Amps: <ul> <li>135.0 single mating end single contact grouping</li> <li>Contact Maximum Ac Voltage Rating In Volts:</li> <li>900.0 single mating end single contact grouping</li> </ul> </li> </ul></li></ul>
<ul> <li>2.094 inches</li> <li>Distance From Mounting Shoulder To Front Face: <ol> <li>1.000 inches</li> </ol> </li> <li>Threaded Device Type: <ul> <li>Back shell and coupling facility</li> </ul> </li> <li>Mating End Quantity: <ul> <li>1</li> </ul> </li> <li>Contact Position Arrangement Style:</li> <li>20-37 single mating end</li> <li>Contact Removability:</li> <li>Removable single mating end single contact grouping</li> <li>Contact Maximum Current Rating In Amps:</li> <li>135.0 single mating end single contact grouping</li> <li>Contact Maximum Ac Voltage Rating In Volts:</li> <li>900.0 single mating end single contact grouping</li> </ul>
2.094 inches Distance From Mounting Shoulder To Front Face: 1.000 inches Threaded Device Type: Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 20-37 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 135.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 900.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 single mating end single contact grouping
2.094 inches Distance From Mounting Shoulder To Front Face: 1.000 inches Threaded Device Type: Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 20-37 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 135.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 900.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 single mating end single contact grouping Polarization Method:



Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 18 and 8 **Thread Size:** 1.613 inches and 2.000 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Plastic phenolic single mating end **Terminal Type:** Crimp and solder single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Anodize **Included Contact Quantity:** 5 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces silver **Precious Material And Weight:** 0.025 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Npt and special acme Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0