
## NSN 5935-00-062-0707

Tip Jack - Page 1 of 2





**Thread Class:** 2a **Thread Direction: Right-hand Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Red **Body Style:** Threaded bushing mounted **Overall Length:** 0.984 inches Mounting Bushing Length: 0.375 inches **Body Length:** 0.734 inches **Overall Diameter:** 0.281 inches **Bushing Accommodation Hole Shape:** Round Maximum Voltage Rating In Volts: 2000.0 ac Accommodated Finger Type: Test prod single finger **Finger Accommodation Diameter:** 0.080 inches single finger Finger Accommodation Length: 0.500 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.250 inches **Capacitance In Picofarads:** 10.0 **Current Rating In Amps:** 15.0 Mounting Facility Type And Quantity: 1 bushing **Thread Size:** 0.250 inches **Terminal Type:** Tab, solder lug Material: Plastic insulator

# NSN 5935-00-062-0707

Tip Jack - Page 2 of 2



Material:

Plastic insulator

#### **Precious Material And Location:**

Spring and terminal surface gold and spring and terminal surface silver

**Precious Material:** 

Gold and silver

## Surface Treatment:

Gold and silver terminal

#### Surface Treatment:

Gold spring and silver spring

### **Thread Series Designator:**

Unef

Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

#### Fiig:

A03400