NSN 5935-00-062-1826

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-062-1826

Body Style:
Straight shape
Overall Length:
2.096 inches
Overall Width:
0.394 inches
Environmental Protection:
Moisture resistant and salt water resistant and shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
2.006 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic polyamide single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
On-n-416 type 2 class 2 federal specification single treatment response

Qq-p-416, type 2, class 2 federal specification single treatment response

Shell Material Specification:

Qq-s-636 federal specification single material response

Included Contact Quantity:

50 single mating end single contact grouping

NSN 5935-00-062-1826

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.050 gold grains, troy and 0.050 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0