NSN 5935-00-062-2020

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-062-2020

| Thread Class: |
|---|
| 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Angle shape w/cable clamp |
| Overall Diameter: |
| 2.463 inches |
| Body Angle In Deg: |
| 90.0 |
| Environmental Protection: |
| Watertight |
| Cable Entrance Diameter: |
| Between 0.922 inches and 1.375 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 36-10 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 13.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 500.0 single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: |
| 700.0 single mating end single contact grouping |
| Polarization Method: |
| Key, multiple key groove |
| Insert Position In Deg: |
| 235.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Internally threaded coupling ring |
| Connector Cable Strain Relief Method: |
| Cable clamp |
| Distance From Centerline To Connector End: |
| 2.874 inches |
| Distance From Centerline To Cable End: |
| |

3.291 inches

NSN 5935-00-062-2020Electrical Plug Connector - Page 2 of 2



| Thready Qty Per Inch (tpi): |
|---|
| 16 |
| Thread Size: |
| 2.250 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| nsert Material: |
| Rubber single mating end |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium and chromate |
| ncluded Contact Quantity: |
| 48 single mating end single contact grouping |
| ncluded Contact Type: |
| Round socket single mating end single contact grouping |
| Special Features: |
| Cord protector |
| Precious Material And Location: |
| Contact surfaces gold and contact surfaces silver |
| Precious Material: |
| Gold and silver |
| Thread Series Designator: |
| Jn |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| 4039b0 |
| |