Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-062-7451

Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.820 inches

Overall Diameter:

1.737 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and shock resistant and cold resistant and heat resistant and explosion proof

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

22-7 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

245.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1250.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1750.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut

Operating Tempurature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Features Provided:

Pre-tinned terminal

Thready Qty Per Inch (tpi):

18 and 18

Thread Size:

1.250 inches and 1.375 inches

NSN 5935-00-062-7451 Electrical Plug Connector - Page 2 of 2



Т	erminal Location:
В	Back single mating end single contact grouping
С	Contact Material:
С	Copper alloy single mating end single contact grouping
С	Contact Surface Treatment:
S	Silver single mating end single contact grouping
lr	nsert Material:
R	Rubber single mating end
С	Contact Surface Treatment Specification:
C	Qq-s-365 federal specification single treatment response single mating end single contact grouping
т	erminal Type:
S	Solder well single mating end single contact grouping
S	Shell Material:
A	sluminum alloy
S	Shell Surface Treatment:
С	Cadmium and chromate
S	Shell Surface Treatment Specification:
C	Qq-p-416, type 2, class 3 federal specification all treatment responses
lr	ncluded Contact Quantity:
1	single mating end single contact grouping
lr	ncluded Contact Type:
R	Round pin single mating end single contact grouping
Ρ	Precious Material And Location:
С	Contact surfaces silver
Ρ	Precious Material And Weight:
0	.005 silver grains, troy
Ρ	Precious Material:
S	Silver
т	hread Series Designator:
U	Jnef and unef
S	Shelf Life:
N	I/a
U	Init Of Measure:
	-
D	Demilitarization:
N	lo
F	iig:
A	039b0